

EL[®]MARK

The Brand of Electricity

MOVABLE RECESSED SPOTLIGHTS DL81F1 SERIES

GENERAL INFORMATION »

- ∴ Rated voltage: 220-240V/ 50-60Hz
- ∴ Power: 15W; 30W; 45W; 60W; 90W
- ∴ Driver: non-isolated driver
- ∴ Colour temperature: 3000K; 4000K
- ∴ Colour body: White
- ∴ Material: Aluminium
- ∴ Beam angle: 24°
- ∴ CRI: Ra≥80
- ∴ Power factor: 0.5
- ∴ Protection level against moisture and dust: IP44



FEATURES »

- ∴ Energy-saving fixture in replacement of fluorescent downlights
- ∴ Safety, low voltage operation
- ∴ Installation in suspended ceilings
- ∴ Pleasant and uniform light distribution
- ∴ Low power consumption
- ∴ Instant light with maximum luminous flux
- ∴ Environmentally friendly - no mercury and lead
- ∴ No ultraviolet and infrared rays
- ∴ Resistant to shock and vibration-free body
- ∴ Modern luminaire designed for hotels, offices, conference halls, museums and restaurants.
- ∴ High degree of protection
- ∴ Lightweight construction





[PRODUCT DETAILS »](#)

Catalogue number	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width (mm)	Height (mm)	Cut hole (mm)	Colour body
92DL81F1530/WH	15	1050	3000	138	138	98	120x120	white
92DL81F1540/WH	15	1050	4000	138	138	98	120x120	white
92DL82F3030/WH	30	2100	3000	176	176	138	160x160	white
92DL82F3040/WH	30	2100	4000	176	176	138	160x160	white
92DL81F3030/WH	2X15	2100	3000	250	138	98	230x120	white
92DL81F3040/WH	2X15	2100	4000	250	138	98	230x120	white
92DL82F6030/WH	2X30	4200	3000	325	176	138	310x160	white
92DL82F6040/WH	2X30	4200	4000	325	176	138	310x160	white
92DL81F4530/WH	3X15	3150	3000	363	138	98	345x120	white
92DL81F4540/WH	3X15	3150	4000	363	138	98	345x120	white
92DL82F9030/WH	3X30	6300	3000	476	176	138	460x160	white
92DL82F9040/WH	3X30	6300	4000	476	176	138	460x160	white

