

ELMARK[®]

The Brand of Electricity

FRAMES FOR LED LAMP and LED LAMPS

GENERAL INFORMATION »

- ∴ Input voltage: 220-240VAC
- ∴ Colour body: White
- ∴ FRAMES Material: Aluminium
- ∴ Led lamps Material: Aluminium + PC
- ∴ Decorative frames are compatible with all LED Lamps 10W & 15W
- ∴ Protection against dust and moisture: IP44
- ∴ Mounting: Recessed
- ∴ Light source: COB LED with a lens of optica

FEATURES »

- ∴ Environmentally friendly - no mercury and lead
- ∴ Modern design
- ∴ Resistant to shock and vibration stable body
- ∴ Low heat emission
- ∴ No ultraviolet and infrared rays

AREAS OF APPLICATION »

- ∴ General illumination
- ∴ Workplaces
- ∴ Hotels
- ∴ Restaurants
- ∴ Home interior





13W

NON-DIMABLE

COLOUR TEMP. 3000K / 4000K

BEAM ANGLE 36° / 60°



18W

DIMMABLE

COLOUR TEMP. 3000K / 4000K

BEAM ANGLE 36° / 60°



PRODUCT DETAILS »

Catalogue number	Model	Type	Diameter Length (mm)	Height (mm)	Cut size(mm)
92A6154	FRAMES FOR LED LAMP 13W/18W	Adjustable	90	34	83
92A6020	FRAMES FOR LED LAMP 13W/18W	Adjustable deep anti-glare round	90	53	83
92A6215	FRAMES FOR LED LAMP 13W/18W	Adjustable deep anti-glare square	90/90	53	80/83
92A6255	FRAMES FOR LED LAMP 13W/18W	Pin-hole	90	37	83

LED LAMPS PRODUCT DETAILS

Catalogue number	Dimmable	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Beam angle
92M6210W36	Non- dimmable	13	1560	4000	36°
92M6210W60	Non- dimmable	13	1430	4000	60°
92M6210WW36	Non- dimmable	13	1560	3000	36°
92M6210WW60	Non- dimmable	13	1430	3000	60°
92M6215W36	Triac- dimmable	18	2160	4000	36°
92M6215W60	Triac- dimmable	18	2000	4000	60°
92M6215WW36	Triac- dimmable	18	2160	3000	36°
92M6215WW60	Triac- dimmable	18	2000	3000	60°

KITS:

Catalogue number	Component-1 Base	Component-2 Frame
92M6210WW366020	92M6210WW36	92A6020
92M6210WW366215	92M6210WW36	92A6215
92M6210WW366154	92M6210WW36	92A6154
92M6210WW366255	92M6210WW36	92A6255
92M6210WW606020	92M6210WW60	92A6020
92M6210WW606215	92M6210WW60	92A6215
92M6210WW606154	92M6210WW60	92A6154
92M6210WW606255	92M6210WW60	92A6255
92M6210W366020	92M6210W36	92A6020
92M6210W366215	92M6210W36	92A6215
92M6210W366154	92M6210W36	92A6154
92M6210W366255	92M6210W36	92A6255
92M6210W606020	92M6210W60	92A6020
92M6210W606215	92M6210W60	92A6215
92M6210W606154	92M6210W60	92A6154
92M6210W606255	92M6210W60	92A6255
92M6215WW366020	92M6215WW36	92A6020
92M6215WW366215	92M6215WW36	92A6215
92M6215WW366154	92M6215WW36	92A6154
92M6215WW366255	92M6215WW36	92A6255
92M6215WW606020	92M6215WW60	92A6020
92M6215WW606215	92M6215WW60	92A6215
92M6215WW606154	92M6215WW60	92A6154
92M6215WW606255	92M6215WW60	92A6255
92M6215W366020	92M6215W36	92A6020
92M6215W366215	92M6215W36	92A6215
92M6215W366154	92M6215W36	92A6154
92M6215W366255	92M6215W36	92A6255
92M6215W606020	92M6215W60	92A6020
92M6215W606215	92M6215W60	92A6215
92M6215W606154	92M6215W60	92A6154
92M6215W606255	92M6215W60	92A6255

DIMENSIONS »

Catalogue number	Diameter/ Length (mm)	Height (mm)
92M6210W36	62	38
92M6210W60	62	38
92M6210WW36	62	38
92M6210WW60	62	38
92M6215W36	62	51
92M6215W60	62	51
92M6215WW36	62	51
92M6215WW60	62	51

ADDITIONAL INFORMATION »

Catalogue number	Barcode	Packing/Box (pcs)
92A6154	3800131241023	1/60
92A6020	3800131241030	1/60
92A6215	3800131241047	1/60
92A6255	3800131241054	1/60
92M6210W36	3800131240989	1/60
92M6210W60	3800131240996	1/60
92M6210WW36		1/60
92M6210WW60		1/60
92M6215W36	3800131241009	1/60
92M6215W60	3800131241016	1/60
92M6215WW36		1/60
92M6215WW60		1/60