

Floodlight Summary:

Report based on lamp delivering 1000 lumens.

Maximum Intensity	2506.3 cd per klm.
(Luminaire orientation as tested.)	0.0 degrees vertical
	-2.5 degrees horizontal

Beam Spread	At 10% of Imax	50.7V x 50.7H
	At 50% of Imax	24.4V x 24.8H
	At 90% of Imax	8.4V x 9.0H

Beam Flux	Total	611.5 lumens per klm.
	To 10% of Imax	521.6 lumens per klm.
	To 50% of Imax	262.5 lumens per klm.
	To 90% of Imax	40.2 lumens per klm.

Upward LOR	0.0 %
Downward LOR	61.2 %


Luminaire Efficiency (Light Output Ratio)	60.9 %
---	--------

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators:
Test Date: 06 October 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.265m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

NAME: 96GRF4/524220	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F65 x 88	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: round	Shielding Angle:



DATA OF LAMP		PHOTOMETRIC DATA	
MODEL	96GRF4/524220	Imax (cd)	877.2
NOMINAL POWER (W)	1	AVAILABILITY (%)	51.7
RATED VOLTAGE (V)	230	Avai. FLUX (lm)	180.8
NOMINAL FLUX (lm)	350	LOR (%)	60.9
LAMPS INSIDE	1	TOTAL FLUX (lm)	213.2
TEST VOLTAGE (V)	230	θ @50% (H,V)	25,24DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM																UNIT:lm		Φ t	Φ a
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.05	0.00
80	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.11	0.00
70	0.00	0.00	0.00	0.01	0.01	0.02	0.02	0.03	0.03	0.03	0.03	0.02	0.01	0.01	0.01	0.00	0.00	0.00	0.22	0.00
60	0.00	0.00	0.00	0.01	0.02	0.03	0.05	0.08	0.10	0.09	0.07	0.04	0.02	0.01	0.01	0.00	0.00	0.00	0.54	0.00
50	0.00	0.00	0.00	0.01	0.03	0.07	0.15	0.29	0.44	0.43	0.28	0.13	0.05	0.02	0.01	0.00	0.00	0.00	1.91	0.00
40	0.00	0.00	0.01	0.02	0.05	0.15	0.46	1.27	2.16	2.16	1.31	0.47	0.12	0.03	0.01	0.00	0.00	0.00	8.24	2.27
30	0.00	0.00	0.01	0.02	0.07	0.30	1.30	3.98	8.06	7.72	3.92	1.40	0.30	0.05	0.02	0.01	0.00	0.00	27.2	23.4
20	0.00	0.00	0.01	0.02	0.09	0.46	2.32	8.82	20.5	18.5	7.79	2.42	0.51	0.07	0.02	0.01	0.00	0.00	61.5	58.5
10	0.00	0.00	0.01	0.02	0.09	0.48	2.45	9.28	20.6	19.1	8.54	2.68	0.58	0.08	0.02	0.01	0.00	0.00	63.9	61.0
0	0.00	0.00	0.01	0.02	0.07	0.33	1.58	4.86	9.53	9.38	4.93	1.85	0.41	0.06	0.02	0.01	0.00	0.00	33.0	29.5
-10	0.00	0.00	0.01	0.02	0.05	0.17	0.64	1.84	3.11	3.25	2.10	0.82	0.18	0.04	0.01	0.00	0.00	0.00	12.2	6.18
-20	0.00	0.00	0.00	0.01	0.03	0.07	0.19	0.46	0.78	0.81	0.52	0.20	0.06	0.02	0.01	0.00	0.00	0.00	3.19	0.00
-30	0.00	0.00	0.00	0.01	0.02	0.03	0.06	0.09	0.13	0.13	0.09	0.05	0.03	0.02	0.01	0.00	0.00	0.00	0.66	0.00
-40	0.00	0.00	0.00	0.01	0.01	0.02	0.02	0.03	0.03	0.03	0.03	0.02	0.02	0.01	0.01	0.00	0.00	0.00	0.24	0.00
-50	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.12	0.00
-60	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.05	0.00
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	-90	-80	-70	-60	-50	-40	-30	-20	HORIZONTAL (DEG)	20	30	40	50	60	70	80	90			
Φ t	0.00	0.02	0.06	0.17	0.53	2.15	9.27	31.1	65.5	61.7	29.6	10.1	2.32	0.44	0.15	0.06	0.02	0.00	213	---
Φ a	0.00	0.00	0.00	0.00	0.00	0.00	3.48	27.1	62.0	58.3	25.8	4.24	0.00	0.00	0.00	0.00	0.00	0.00	---	181

one-half-peak spread: U:12.8,D:11.7 , L:10.7,R:14.3


NEMA Beam Type: Type 4

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:06 October 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

NAME: 96GRF4/524220	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F65 x 88	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: round	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators:
Test Date: 06 October 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.265m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


NAME: 96GRF4/524220	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F65 x 88	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: round	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators:
Test Date: 06 October 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.265m [K=1.0000]
Remarks:

Planar Illuminance Curve




C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators:
 Test Date: 06 October 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

AAI Figure

NAME: 96GRF4/524220	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F65 x 88	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: round	Shielding Angle:



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators:
 Test Date: 06 October 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 96GRF4/524220	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F65 x 88	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: round	Shielding Angle:

Table--1

UNIT: cd

H (DEG) V (DEG)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-85	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.00	0.01	0.02	0.01	0.00	0.01	0.02	0.01	0.00
-80	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.03	0.05	0.05	0.05	0.07	0.09	0.09	0.08	0.10	0.11	0.10	0.09
-75	0.00	0.00	0.00	0.01	0.03	0.04	0.05	0.07	0.10	0.12	0.12	0.14	0.17	0.18	0.17	0.19	0.21	0.20	0.20
-70	0.00	0.00	0.00	0.02	0.06	0.08	0.09	0.13	0.17	0.19	0.20	0.23	0.26	0.28	0.28	0.30	0.33	0.32	0.31
-65	0.00	0.00	0.00	0.04	0.09	0.12	0.14	0.18	0.23	0.27	0.30	0.33	0.38	0.40	0.42	0.45	0.48	0.48	0.47
-60	0.00	0.00	0.01	0.06	0.11	0.16	0.19	0.24	0.30	0.37	0.41	0.45	0.52	0.58	0.61	0.66	0.70	0.71	0.70
-55	0.00	0.00	0.02	0.07	0.14	0.20	0.25	0.30	0.39	0.48	0.55	0.63	0.73	0.83	0.90	0.98	1.04	1.07	1.06
-50	0.00	0.00	0.03	0.09	0.16	0.24	0.31	0.38	0.49	0.61	0.74	0.88	1.04	1.22	1.38	1.53	1.64	1.69	1.69
-45	0.00	0.00	0.04	0.11	0.18	0.27	0.37	0.47	0.60	0.77	0.99	1.22	1.52	1.91	2.38	2.91	3.42	3.75	3.83
-40	0.00	0.00	0.05	0.12	0.21	0.31	0.43	0.56	0.73	0.98	1.30	1.73	2.43	3.37	4.62	6.12	8.03	9.05	9.10
-35	0.00	0.00	0.06	0.13	0.23	0.34	0.49	0.66	0.90	1.22	1.71	2.60	3.98	6.17	9.39	14.2	19.8	23.7	25.4
-30	0.00	0.01	0.07	0.15	0.25	0.37	0.54	0.77	1.07	1.51	2.44	4.05	6.86	11.4	19.3	30.9	44.0	52.8	57.3
-25	0.00	0.01	0.08	0.16	0.27	0.40	0.59	0.86	1.25	1.86	3.47	6.25	11.3	20.9	38.1	59.8	83.6	100	109
-20	0.00	0.01	0.08	0.17	0.28	0.43	0.63	0.94	1.42	2.46	4.68	9.01	17.9	35.8	64.5	102	141	172	186
-15	0.00	0.01	0.09	0.18	0.30	0.45	0.67	1.02	1.63	3.01	5.88	11.8	25.9	54.6	98.1	157	235	311	336
-10	0.00	0.01	0.09	0.19	0.31	0.47	0.70	1.08	1.81	3.48	7.13	15.1	34.0	71.4	131	229	389	520	562
-5	0.00	0.01	0.09	0.19	0.31	0.47	0.71	1.11	1.93	3.74	7.82	17.1	39.5	83.8	163	304	540	717	760
0	0.00	0.01	0.09	0.20	0.32	0.47	0.72	1.12	1.97	3.80	7.91	17.3	40.9	88.9	177	335	619	823	871
5	0.00	0.01	0.09	0.20	0.32	0.48	0.72	1.12	1.94	3.71	7.59	16.2	37.2	81.8	152	287	529	725	761
10	0.00	0.01	0.09	0.20	0.32	0.47	0.71	1.09	1.84	3.43	6.79	13.9	30.2	63.2	116	196	347	494	528
15	0.00	0.01	0.09	0.19	0.31	0.46	0.68	1.03	1.67	2.96	5.59	10.7	21.4	43.6	82.2	128	189	252	270
20	0.00	0.01	0.09	0.19	0.30	0.44	0.64	0.93	1.43	2.46	4.43	7.90	14.2	26.7	48.4	76.9	108	132	138
25	0.00	0.01	0.09	0.18	0.29	0.41	0.58	0.84	1.23	1.94	3.32	5.63	9.27	15.0	25.3	40.6	56.3	67.9	72.6
30	0.00	0.01	0.08	0.17	0.27	0.38	0.52	0.73	1.04	1.51	2.39	3.83	6.00	8.72	12.8	18.8	25.7	30.4	32.4
35	0.00	0.01	0.07	0.16	0.24	0.33	0.46	0.63	0.87	1.19	1.68	2.54	3.71	5.19	6.97	8.98	11.2	12.7	13.1
40	0.00	0.01	0.07	0.15	0.22	0.29	0.40	0.54	0.73	0.94	1.22	1.64	2.25	3.02	3.89	4.68	5.51	5.95	5.93
45	0.00	0.01	0.06	0.13	0.19	0.25	0.34	0.46	0.60	0.74	0.91	1.13	1.39	1.73	2.12	2.46	2.78	2.95	2.94
50	0.00	0.01	0.05	0.11	0.16	0.21	0.29	0.39	0.48	0.58	0.69	0.82	0.95	1.08	1.23	1.38	1.47	1.52	1.54
55	0.00	0.00	0.04	0.09	0.13	0.17	0.25	0.32	0.38	0.44	0.52	0.61	0.67	0.73	0.81	0.88	0.92	0.95	0.98
60	0.00	0.00	0.03	0.06	0.10	0.14	0.20	0.26	0.29	0.33	0.39	0.45	0.48	0.51	0.56	0.59	0.61	0.64	0.66
65	0.00	0.00	0.02	0.05	0.07	0.11	0.16	0.19	0.22	0.24	0.29	0.32	0.33	0.36	0.40	0.41	0.41	0.43	0.45
70	0.00	0.00	0.01	0.03	0.04	0.07	0.11	0.13	0.15	0.18	0.21	0.23	0.23	0.25	0.28	0.28	0.28	0.29	0.31
75	0.00	0.00	0.00	0.01	0.01	0.04	0.07	0.08	0.08	0.11	0.14	0.15	0.14	0.16	0.18	0.18	0.17	0.19	0.20
80	0.00	0.00	0.00	0.00	0.00	0.02	0.03	0.03	0.03	0.05	0.07	0.07	0.06	0.08	0.10	0.09	0.08	0.10	0.11
85	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.02	0.01	0.01	0.02	0.03	0.02	0.01	0.02	0.03
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature:25.3°C

Operators:

Test Date:06 October 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456

Humidity:65.0%

Test Distance:6.265m [K=1.0000]

Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 96GRF4/524220	TYPE:	WEIGHT: 1
SPEC.:	DIM.: F65 x 88	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: round	Shielding Angle:

Table--2

UNIT: cd

H (DEG) V (DEG)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-85	0.01	0.03	0.01	0.00	0.01	0.02	0.01	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-80	0.10	0.11	0.09	0.08	0.08	0.09	0.06	0.04	0.05	0.05	0.02	0.00	0.01	0.01	0.00	0.00	0.00	0.00	
-75	0.20	0.21	0.19	0.17	0.17	0.17	0.14	0.12	0.11	0.10	0.07	0.04	0.03	0.02	0.01	0.00	0.00	0.00	
-70	0.32	0.32	0.30	0.28	0.28	0.26	0.23	0.20	0.18	0.16	0.12	0.08	0.07	0.05	0.01	0.00	0.00	0.00	
-65	0.48	0.48	0.44	0.41	0.40	0.37	0.32	0.29	0.26	0.23	0.17	0.13	0.11	0.08	0.03	0.00	0.00	0.00	
-60	0.71	0.69	0.64	0.60	0.56	0.51	0.44	0.40	0.36	0.29	0.23	0.18	0.15	0.10	0.04	0.00	0.00	0.00	
-55	1.06	1.02	0.94	0.86	0.79	0.69	0.59	0.53	0.46	0.37	0.29	0.24	0.19	0.13	0.06	0.01	0.00	0.00	
-50	1.68	1.61	1.48	1.28	1.12	0.94	0.80	0.69	0.57	0.45	0.36	0.29	0.23	0.15	0.08	0.03	0.00	0.00	
-45	3.65	3.28	2.77	2.23	1.67	1.31	1.07	0.88	0.70	0.55	0.44	0.35	0.26	0.17	0.09	0.04	0.01	0.00	
-40	8.64	7.82	6.07	4.48	3.19	2.15	1.44	1.11	0.86	0.66	0.52	0.40	0.29	0.20	0.11	0.05	0.01	0.00	
-35	24.3	21.2	15.0	10.0	6.23	3.90	2.21	1.42	1.04	0.79	0.60	0.45	0.32	0.22	0.13	0.06	0.01	0.00	
-30	56.3	49.2	36.6	24.3	13.7	7.30	3.88	2.01	1.27	0.93	0.68	0.49	0.35	0.23	0.15	0.07	0.01	0.00	
-25	105	91.5	70.3	48.2	27.3	13.7	6.41	3.03	1.53	1.07	0.75	0.53	0.37	0.25	0.16	0.08	0.01	0.00	
-20	178	148	112	77.1	46.1	23.5	10.1	4.32	1.99	1.20	0.82	0.56	0.40	0.27	0.17	0.08	0.02	0.00	
-15	308	231	162	107	65.1	33.7	14.0	5.65	2.49	1.36	0.88	0.60	0.42	0.29	0.18	0.09	0.02	0.00	
-10	493	355	225	139	82.4	42.6	18.5	7.13	2.94	1.49	0.94	0.64	0.44	0.31	0.19	0.10	0.02	0.00	
-5	659	476	284	166	95.2	48.3	20.3	7.81	3.12	1.55	0.98	0.66	0.46	0.32	0.20	0.10	0.02	0.00	
0	724	516	298	164	94.5	47.5	19.8	7.75	3.11	1.56	1.00	0.67	0.47	0.32	0.20	0.10	0.02	0.00	
5	642	442	256	145	84.5	42.8	18.1	7.05	2.88	1.49	0.97	0.66	0.46	0.32	0.20	0.10	0.02	0.00	
10	453	309	187	117	69.4	34.2	14.6	5.91	2.49	1.37	0.91	0.63	0.45	0.31	0.20	0.10	0.02	0.00	
15	243	184	129	84.6	48.2	23.6	10.5	4.57	2.07	1.24	0.85	0.60	0.43	0.30	0.19	0.10	0.02	0.00	
20	129	108	80.3	51.3	29.0	14.5	7.00	3.40	1.66	1.10	0.77	0.56	0.41	0.29	0.19	0.10	0.02	0.00	
25	69.3	57.7	42.0	26.5	15.1	8.43	4.50	2.33	1.37	0.96	0.69	0.51	0.38	0.27	0.18	0.09	0.02	0.00	
30	30.4	25.5	19.3	12.6	7.95	4.83	2.78	1.63	1.15	0.83	0.61	0.46	0.34	0.25	0.17	0.08	0.02	0.00	
35	12.5	10.8	8.51	6.17	4.23	2.76	1.76	1.26	0.94	0.71	0.54	0.41	0.30	0.22	0.15	0.08	0.01	0.00	
40	5.71	5.04	4.11	3.25	2.38	1.72	1.27	0.97	0.77	0.61	0.47	0.35	0.27	0.20	0.14	0.07	0.01	0.00	
45	2.81	2.53	2.15	1.80	1.44	1.17	0.94	0.75	0.61	0.51	0.41	0.31	0.23	0.17	0.12	0.06	0.01	0.00	
50	1.50	1.42	1.31	1.14	0.98	0.84	0.71	0.58	0.49	0.42	0.35	0.27	0.20	0.14	0.10	0.05	0.01	0.00	
55	0.96	0.91	0.87	0.78	0.68	0.60	0.53	0.45	0.38	0.34	0.29	0.23	0.16	0.11	0.08	0.03	0.00	0.00	
60	0.64	0.62	0.59	0.55	0.48	0.44	0.41	0.35	0.29	0.26	0.23	0.18	0.13	0.09	0.06	0.02	0.00	0.00	
65	0.44	0.42	0.41	0.39	0.35	0.32	0.30	0.27	0.23	0.20	0.18	0.14	0.09	0.06	0.04	0.02	0.00	0.00	
70	0.30	0.28	0.28	0.27	0.24	0.22	0.22	0.20	0.16	0.13	0.12	0.10	0.06	0.03	0.01	0.01	0.00	0.00	
75	0.19	0.17	0.18	0.18	0.16	0.14	0.14	0.13	0.10	0.07	0.07	0.06	0.03	0.00	0.01	0.00	0.00	0.00	
80	0.09	0.08	0.09	0.10	0.08	0.06	0.06	0.06	0.04	0.02	0.03	0.02	0.01	0.00	0.00	0.00	0.00	0.00	
85	0.02	0.01	0.02	0.03	0.01	0.00	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature:25.3°C

Operators:

Test Date:06 October 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456

Humidity:65.0%

Test Distance:6.265m [K=1.0000]

Remarks: